

## SAFETY DATA SHEET Air Tool Lubricant

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

## 1. Identification

## **Product identifier**

Product name Air Tool Lubricant

**Product number** L0713-062, L0713-054, L0713-054A, L0713-057, L0713-060, L0713-061

## Recommended use of the chemical and restrictions on use

**Application** Lubricating oil

Uses advised against No specific uses advised against are identified.

## Details of the supplier of the safety data sheet

Manufacturer Lubriplate Lubricants Co.

Corporate Headquarters 129 Lockwood Street Newark, NJ 07105

Midwest Office & Plant 1500 Oakdale Ave. Toledo, OH 43605 419-691-2491 419-693-3806

## Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)

01-813-248-0585 (Outside US & Canada)

## 2. Hazard(s) identification

## Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

## **Mixtures**

## Air Tool Lubricant

## Distillates (petroleum), hydrotreated heavy naphthenic

30-60%

CAS number: 64742-52-5

Classification
Not Classified

The full text for all hazard statements is displayed in Section 16.

Composition comments \* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## 4. First-aid measures

## Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Skin Contact Remove affected person from source of contamination. Rinse immediately with plenty of

water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

#### Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

**Inhalation** Prolonged inhalation of high concentrations may damage respiratory system.

**Ingestion** Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

**Skin contact** Prolonged contact may cause dryness of the skin.

**Eye contact** May cause temporary eye irritation.

#### Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

Specific treatments No special treatment required.

## 5. Fire-fighting measures

## Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

## Special hazards arising from the substance or mixture

## Air Tool Lubricant

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

- Orderial productions, procedure equipment and emergency procedures

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.

**Environmental precautions** 

Personal precautions

**Environmental precautions** 

Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

## Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

#### 7. Handling and storage

#### Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

### Air Tool Lubricant

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local

regulations.

Storage class Unspecified storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

### 8. Exposure controls/Personal protection

## Control parameters

#### Occupational exposure limits

#### Distillates (petroleum), hydrotreated heavy naphthenic

Mineral oil, excluding metal working fluids (pure, highly and severely refined) ACGIH

ACGIH = American Conference of Governmental Industrial Hygienists.

## **Exposure controls**

## Protective equipment





# Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

## Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. The following protection should be worn: Chemical splash goggles.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

## Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

## Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

# Environmental exposure controls

Not regarded as dangerous for the environment.

## 9. Physical and chemical properties

#### Information on basic physical and chemical properties

### Air Tool Lubricant

Appearance Liquid.

Color Amber.

Odor Mild.

Odor threshold Not available.

pH Not available.

Melting point Not available.

Initial boiling point and range >288°C (>550.4°F)

Flash point > 196°C/384.8°F Cleveland open cup.

**Evaporation rate** < 0.01 (butyl acetate = 1)

Upper/lower flammability or

explosive limits

Not available.

Not available.

Vapor pressure <0.67 kPa @ 25°C

Vapor density > 5

Relative density 0.88

Solubility(ies) Insoluble in water.

Partition coefficient

Auto-ignition temperature

Decomposition Temperature

Viscosity

Not available.

Not available.

Not available.

Not available.

Not available.

Not applicable.

Other information None.

## 10. Stability and reactivity

Oxidizing properties

**Reactivity** See the other subsections of this section for further details.

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

No potentially hazardous reactions known.

**Conditions to avoid** There are no known conditions that are likely to result in a hazardous situation.

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

## 11. Toxicological information

## Information on toxicological effects

### Air Tool Lubricant

**Toxicological effects** Not regarded as a health hazard under current legislation.

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

Skin corrosion/irritation

**Animal data**Based on available data the classification criteria are not met.

Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

**Aspiration hazard**Based on available data the classification criteria are not met.

General information No specific health hazards known. The severity of the symptoms described will vary

dependent on the concentration and the length of exposure.

**Inhalation** Prolonged inhalation of high concentrations may damage respiratory system.

**Ingestion** Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

**Skin Contact** Prolonged contact may cause dryness of the skin.

**Eye contact** May cause temporary eye irritation.

Route of exposure Ingestion Inhalation Skin and/or eye contact

### Air Tool Lubricant

**Target Organs** No specific target organs known.

12. Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

**Mobility** No data available.

Other adverse effects

Other adverse effects None known.

## 13. Disposal considerations

## Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and

any local authority requirements.

**Disposal methods**Dispose of surplus products and those that cannot be recycled via a licensed waste disposal

contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water

authority.

## 14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, DOT).

UN Number

UN No. (International) Not applicable.

UN proper shipping name

Proper shipping name (International)

Not applicable.

Transport hazard class(es)

Transport Labels (International)

No transport warning sign required.

Transport labels

No transport warning sign required.

## Air Tool Lubricant

## **DOT transport labels**

No transport warning sign required.

### Packing group

Packing group (International) Not applicable.

### **Environmental hazards**

### **Environmentally Hazardous Substance**

No.

### Special precautions for user

Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

### 15. Regulatory information

## **US Federal Regulations**

## SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

## CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

## SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

## SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Zinc alkyldithiophosphate

1.0 %

Dec-1-ene, homopolymer, hydrogenated.dec-1-ene, oligomers, hydrogenated

1.0 %

## **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

## FDA - Essential Chemical

None of the ingredients are listed or exempt.

## FDA - Precursor Chemical

None of the ingredients are listed or exempt.

## SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

## **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

## **US State Regulations**

### Air Tool Lubricant

#### California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

## California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

## California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

#### California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

## Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Distillates (petroleum), hydrotreated light naphthenic

### Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

## Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

### New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

## Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

#### **Inventories**

## US - TSCA

All the ingredients are listed or exempt.

Zinc alkyldithiophosphate

Distillates (petroleum), hydrotreated heavy paraffinic

alkyl naphthalene sulfonic acid, calcium salt

Distillates (petroleum), hydrotreated middle

Distillates (petroleum), hydrotreated heavy naphthenic

Distillates (petroleum), hydrotreated light naphthenic

Soy methyl esters

## US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

## 16. Other information

**Training advice** Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

**Revision comments** Rereleased through new GHS Software.

Revision date 5/22/2017

Revision 1.01

Supersedes date 3/10/2015

**SDS No.** 4830

## **Air Tool Lubricant**

**End of SDS** 

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.